



# Coe Lanie



## RICHARDS BAY

Procedure No.	SOP 06 PP
Revision	0
Pages	1 OF 2

### SOP 06 PP- POLE PRUNER

#### TABLE OF CONTENTS

1. PURPOSE.....	2
2. SCOPE.....	2
3. RESPONSIBILITY, ACCOUNTABILITY AND AUTHORISATION.....	2
4. DEFINITIONS & ABBREVIATIONS.....	2
5. SAFETY, HEALTH, ENVIROMENTAL & QUALITY.....	2
6. PROCEDURE.....	2
7. RECORDS.....	3

#### REVISION SHEET

REVISION NUMBER	SUBJECT OF REVISION	PAGE NUMBER	EFFECTIVE DATE
0	New Procedure	All	16/07/2010

#### ENDORSEMENT

	DESIGNATION	DATE	SIGNATURE
REVIEWED BY	OWNER	16/7/10	
CHECKED BY	OWNER	16/7/10	
APPROVED BY	OWNER	16/7/10	



EYE & HEARING PROTECTION MUST BE WORN



PROTECTIVE CLOTHING MUST BE WORN



DUST MASK MUST BE WORN



FOOT PROTECTION MUST BE WORN



HAND PROTECTION MUST BE WORN

To ensure the safe operating of a Pole Pruner

2. **SCOPE**

Applies to all blower operators

3. **RESPONSIBILITY, ACCOUNTABILITY AND AUTHORISATION**

The Supervisor /operator to be convinced that the procedure poses no threat to himself, other people, surrounding buildings and or vehicles. Ensure that no person or animal is endangered when operating the Pole Pruner.

4. **DEFINITIONS & ABBREVIATIONS**

None

5. **SAFETY, HEALTH, ENVIROMENTAL & QUALITY  
ALWAYS WEAR PERSONAL PROTECTIVE**

**When using the product, you should wear proper clothing and protective equipment.**

- Helmet
- Protection goggles or face protector
- Ear protectors
- Thick work gloves
- Non-slip sole work boots
- When using your pole pruner, always wear strong, durable, work clothing; shirts should be long-sleeved and trousers should be full-length.

6. **PROCEDURE**

1. Supervisors shall verify that operators are capable and qualified on each type of equipment before allowing the equipment to be operated unsupervised.
2. Operators shall perform a pre-operational check of equipment. Be familiar with operator's manual. Report all needed repairs promptly and do not use any equipment that is unsafe.
3. Clothing must be snug-fitting, but allow complete freedom of movement. Avoid loose-fitting clothing such as safety vests, jackets, scarves, jewelry, flared or cuffed pants or anything that could become entangled in pruner. Orange colored clothing such as bright orange tee shirts shall be substituted for safety vests.
4. Take frequent breaks. If you lack sufficient strength to maintain control, do not use it.
5. Always stop engine before putting a pole pruner down or carrying it. Accidental acceleration can cause chain to rotate and can be extremely dangerous while carrying it.
6. The muffler and other parts of the engine become hot during operation and remain hot after stopping the engine. To reduce the risk of burns, do not touch parts while they are hot.
7. The chain guard must be used when walking with or transporting the pruner.
8. Proper chain tension is extremely important. Follow tensioning procedures as described in the operator's manual. Never start with the sprocket cover loose. Never try to tighten chain while the engine is running.
9. Fuel in a well-ventilated area, outdoors only. Shut off engine and allow it to cool. Remove fuel cap carefully so as to allow any pressure build-up in the tank to slowly release. Select bare ground and move at least 10' from fueling spot before starting engine. Wipe off any excess fuel prior to starting. Do not allow other persons to be near. Keep bystanders at least 50' (feet) away. Operate in outdoors in a ventilated area.

clearance between pruner and any electrical line. Keep pruner on firm ground or other solid surface when starting.

11. Do not cut any material other than wood or wooden objects. Objects such as rocks, fences, nails, etc. can be flung off and injure the operator or bystanders.
12. Keep work area clean and clear of any debris such as fallen limbs or other obstacles that could cause tripping and stumbling hazards.
13. Do not cut vertically from your body. Hold the pole pruner at an angle of not more than 60° from the horizontal level. **DO NOT STAND DIRECTLY UNDERNEATH THE LIMB BEING CUT!**
14. If bar becomes pinched and caught in the branch so that the chain can no longer move, shut off the pruner and carefully move the branch to open the pinch and release the bar.
15. Prune large diameter branches in several controllable pieces. If branch is more than 4" in diameter, first perform undercut and then cross-cut at a distance of about 8" from the final cut. Then carry out the flush-cut, starting with a relieving cut and finishing with a cross-cut.
16. During emergency operations, look for downed utility lines before using cutting with pruner.
17. Always maintain firm foothold. Be extremely cautious when working on slopes or uneven ground. Never work from the bed of a dump truck. Never work on a ladder, tree or any other insecure object. When working at a height above 15' use a lift bucket. For pruners with adjustable shafts, expand the shaft only as far as intended for the application.

## 7. RECORDS

None